

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) UK Patent Application (19) GB (11) 2 236 184 (13) A

(43) Date of A publication 27.03.1991

(21) Application No 8920638.5

(22) Date of filing 12.09.1989

(71) Applicant
Finnigan Mat Ltd

(Incorporated in the United Kingdom)

Paradise, Hemel Hempstead, Herts, HP2 4TG,
United Kingdom

(72) Inventors
John S Cottrell
Kuldip K Mock

(74) Agent and/or Address for Service
Boulton Wade & Tennant
27 Fumival Street, London, EC4A 1PQ,
United Kingdom

(51) INT CL³
G01N 1/28

(52) UK CL (Edition K)
G1B BCH
U1S S1909

(56) Documents cited
None

(58) Field of search
UK CL (Edition J) G1B BBG BCF BCH
INT CL³ G01N
On line databases: WPI AND CLAIMS

(54) Preparing a sample for laser spectrometry analysis

(57) A sample for analysis by Laser Desorption Mass Spectrometry is prepared by dissolving the sample material in a solvent and applying the solution to a matrix material applied to a target for a mass spectrometer. The matrix material is selected from the group consisting of (i) Cinnamic Acid, either *cis* or *trans*, with the aromatic ring substituted by one or more groups which possess an electron pair on the atom adjacent to the ring; (ii) Benzoic Acid, with one or more substituent groups as described in (i); (iii) Coumarin, with one or more substituent groups as described in (i).

GB 2 236 184 A

METHOD OF PREPARING A SAMPLE FOR ANALYSIS

This invention relates to a method of preparing a sample for analysis, and particularly a sample for analysis by Laser Desorption Mass Spectrometry (LDMS) in which ions are sputtered from a condensed phase sample surface by photon bombardment and are then subjected to mass analysis.

Many methods of LDMS are known, and a feature common to many is the use of a matrix material in which the analyte (the sample material to be analysed) is dispersed. The matrix material can serve one or more of a plurality of functions. For example it may act as a mediator in transferring energy from the photon bombardment to the sample material molecules; it may provide a physical and chemical environment which enhances the probability of desorption in the desired state of charge and aggregation; it may remove excess energy from the desorbed species through evaporation of matrix material molecules from a desorbed cluster of sample material and matrix material ions; and it may assist in the isolation and purification of the sample material.

Four techniques for using a matrix material to enhance LDMS have been described as set out below.

The first is to dissolve the sample material together with a 10:1 excess of an inorganic salt in a solvent, place a

drop of the solution on the target surface, and evaporate to dryness as described by D.V. Davis et. al. in Analytical Chemistry, 55 1302 (1983). The sample material deposit is then irradiated with infra-red photons from a pulsed Neodymium YAG laser.

The second is to mix equimolar amounts of sample material and an inorganic salt in a droplet of glycerol placed on the target surface as described by L.G. Wright et. al. in Biomedical Mass Spectrometry, 12 159 (1985). The sample mixture is then irradiated with infra-red photons from a continuous wave carbon dioxide laser.

Thirdly, Japanese Patent Specification JP62-43562 discloses a sample preparation technique in which a solution of the sample material is mixed with a slurry of glycerol and fine cobalt powder. A droplet of the mixture is then irradiated with ultraviolet photons from a pulsed nitrogen laser.

Fourthly, M. Karas et. al. (Int. J. Mass Spectrom. Ion Processes, 78 53 (1987)) describe using a large molar excess of a matrix material which has a strong absorption at the wavelength of the incident radiation. For example, the sample material is dissolved in a solution containing a thousand-fold molar excess of Nicotinic Acid. A drop of the solution is placed on the target surface, evaporated to dryness, and irradiated with 266nm ultraviolet photons from a frequency quadrupled pulsed Neodymium YAG laser. The use of a matrix material which has a strong absorption for the incident photons

represents an important distinction between this approach and the first three described because it allows the use of low power densities which increases the probability of desorbing intact molecular ions.

The use of 266nm photons and a Nicotinic Acid matrix material as described in M. Karas et. al. mentioned above has been shown to provide excellent sensitivity. A drawback of the technique is that suitable sources of 266nm photons are complex and expensive. The commonly used sources are a Q switched, frequency quadrupled Neodymium YAG laser or an excimer pumped, frequency doubled dye laser.

According to this invention there is provided a method of preparing a sample for analysis by laser desorption mass spectrometry, comprising dissolving the sample material in a solvent and applying the solution to a matrix material applied to a target for a mass spectrometer, in which the matrix material is selected from the group consisting of (i) Cinnamic Acid, either cis or trans, with the aromatic ring substituted by one or more groups which possess an electron pair on the atom adjacent to the ring; (ii) Benzoic Acid, with one or more substituent groups as described in (i); (iii) Coumarin, with one or more substituent groups as described in (i).

The method of this invention gives the advantage that it enables the use of relatively long wavelength photons, in particular 337nm light from a commonly available nitrogen

laser, for the photon bombardment, rather than it being necessary to use lasers as mentioned above.

The matrix material can be one of:-

- 2, 4-Dimethoxycinnamic Acid
- 3, 4-Dimethoxycinnamic Acid
- 3, 4-Dihydroxycinnamic Acid
- 4-Hydroxy-3-methoxycinnamic Acid
- 3-Hydroxy-4-methoxycinnamic Acid
- 3, 5-Dimethoxy-4-hydroxycinnamic Acid

Otherwise the matrix material can be Anthranilic Acid or Scopoletin.

This invention will now be described by way of example.

A matrix material selected from the group specified is dissolved in an appropriate solvent system, generally water, at a concentration of (say) 5×10^{-2} molar. A small aliquot of a solution of the sample in a compatible solvent system, for example a 10^{-5} molar solution of a peptide in 0.1% aqueous Trifluoroacetic Acid, is mixed with an aliquot of the matrix solution and applied to a target for a mass spectrometer. Alternatively, the two solutions may be mixed directly on the target surface. The mixed solution is evaporated to dryness and the prepared target introduced into the source region of the mass spectrometer for analysis by bombardment with 337nm photons from a nitrogen laser.

CLAIMS

1. A method of preparing a sample for analysis by laser desorption mass spectrometry, comprising dissolving the sample material in a solvent and applying the solution to a matrix material applied to a target for a mass spectrometer, in which the matrix material is selected from the group consisting of (i) Cinnamic Acid, either cis or trans, with the aromatic ring substituted by one or more groups which possess an electron pair on the atom adjacent to the ring; (ii) Benzoic Acid, with one or more substituent groups as described in (i); (iii) Coumarin, with one or more substituent groups as described in (i).

2. A method as claimed in Claim 1, in which the matrix material is one of:-

2, 4-Dimethoxycinnamic Acid

3, 4-Dimethoxycinnamic Acid

3, 4-Dihydroxycinnamic Acid

4-Hydroxy-3-methoxycinnamic Acid

3-Hydroxy-4-methoxycinnamic Acid

3, 5-Dimethoxy-4-hydroxycinnamic Acid

3. A method as claimed in Claim 1, in which the matrix material is Anthranilic Acid.

4. A method as claimed in Claim 1, in which the matrix material is Scopoletin.